



SKU/Part Number: B-SX8

Thermal Transfer/Direct Thermal

305dpi up to 8" per second

Technology

Thermal Transfer/Direct Thermal

Resolution

12.05 dots/mm (306 dpi)

Dimensions

416 (W) x 289 (D) x 395 (H) mm

Weight

25 kg (without media and ribbon)

Printhead

Edge Type

Print Width

Maximum 213.3 mm

Print Length

Maximum 1364 mm

Print Speed (Standard)

Up to 203 mm/s

Emulation

Zebra (ZPL)

Interface

Bidirectional parallel port, USB 2.0, LAN (100BASE), serial port*, wireless LAN*

Barcodes

UPC/EAN/JAN, Code 39, Code 93, Code 128, EAN 128, NW7, MSI Industrial 2 of 5, ITF, Postnet, RM4SCC, KIX-code, RSS14, Customer Bar Code

2D Codes

DataMatrix, PDF 417, Maxicode, QR code, Micro PDF 417, CP Code

Fonts

Bitmap font (21 fonts), Outline font (4 types), Price font (3 types)

Options

Cutter module, strip module, ribbon save module (standard on B-SX8), wireless LAN module, serial interface board, expansion I/O board, RTC (real time clock), metal cover **, RFID kit**